PRIMER

ACRYLIC PRIMER

LUNIK
COATING CULTURE

TECHNICAL DATA SHEET

Description

Primer formulated with water-based acrylic copolymers. Dilutable with water and stable in alkaline media, it is compatible with cement, lime and, in general, with all hydraulic binders. Formulated for both porous and non-porous supports. High resistance to water and alkalis.

Applications

- Primer for microcements, mortar-concrete, mortar-mortar, plaster-concrete, plaster-mortar, plaster-plaster and concrete-concrete.
- Ideal for partition walls, wrought iron fronts, large plastering on concrete walls and facades, plastering on vertical or horizontal surfaces, plasterboard, etc.
- Union bridge for transparent layers such as polyurethane varnishes.
- Enhances adhesion and waterproofing of colored joints, even in porcelain stoneware.

Surface Preparation

The support must be free of dust and grease. In the case of concrete, in addition, the support must be firm (minimum tensile strength of 1.5 N/mm2) and dry (maximum humidity allowed 4%).

Application

It can be applied by roller, brush or spray. It can be applied as supplied or diluted with a maximum of 50% water. The application must be carried out at a support temperature 3°C higher than the dew point, with an ambient temperature higher than 10°C and a humidity lower than 80%. It does not need special precautions for its use.

Storage

PRIMER is presented in hermetic containers and approved in accordance with the EU guidelines for the packaging and storage of chemical products. Avoid frost and temperatures above 35° C. The product can be stored for one year in original and closed containers and covered places.

Precautions

In case of contact with eyes, wash them with plenty of clean water and consult a doctor. Hands and skin should be washed with soap and hot water. Avoid release to the environment.

www.lunik.cc

Calle Benifaió 38, Guadassuar (Valencia)
46610 Spain
Tel. +34 96 052 85 03

The indications and technical data that appear in this brochure are based on our current knowledge and on the most typical uses and applications of the product and are for guidance only, and may be subject to changes and modifications without prior notice. Depending on the commissioning conditions, in which we have no participation, the specific values may suffer certain variations, as well as normal differences in manufacturing tolerances, tests carried out, etc. For this reason, our guarantee is limited solely to the quality of the product supplied.